This XML file does not appear to have any style information associated with it. The document tree is shown below.

```xml
<!--
  Published by JAX-WS RI (http://jax-ws.java.net). RI's version is JAX-WS RI 2.2.9-b130926.1035 svn-revision#5f6196f2b90e9460065a4c2f4e30e065b245e51e.
-->
<!--
  Generated by JAX-WS RI (http://jax-ws.java.net). RI's version is JAX-WS RI 2.2.9-b130926.1035 svn-revision#5f6196f2b90e9460065a4c2f4e30e065b245e51e.
-->
<definitions xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd" xmlns:wsp="http://www.w3.org/ns/ws-policy"
xmlns:wsp1_2="http://schemas.xmlsoap.org/ws/2004/09/policy" xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" xmlns:tns="http://server.kanif.softwaretestingclass.com/"
xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns="http://schemas.xmlsoap.org/wsdl/" targetNamespace="http://server.kanif.softwaretestingclass.com/"
name="WebServiceImplementService">
  <types/>
  <message name="getUIDPassword">
    <part name="arg0" type="xsd:string"/>
    <part name="arg1" type="xsd:string"/>
    <part name="arg2" type="xsd:string"/>
    <part name="arg3" type="xsd:string"/>
    <part name="arg4" type="xsd:string"/>
  </message>
  <message name="getUIDPasswordResponse">
    <part name="return" type="xsd:string"/>
  </message>
  <portType name="IWebService">
    <operation name="getUIDPassword" parameterOrder="arg0 arg1 arg2 arg3 arg4">
      <input wsam:Action="http://server.kanif.softwaretestingclass.com/IWebService/getUIDPasswordRequest" message="tns:getUIDPassword"/>
      <output wsam:Action="http://server.kanif.softwaretestingclass.com/IWebService/getUIDPasswordResponse" message="tns:getUIDPasswordResponse"/>
    </operation>
  </portType>
  <binding name="WebServiceImplementPortBinding" type="tns:IWebService">
    <soap:binding transport="http://schemas.xmlsoap.org/soap/http" style="rpc"/>
    <operation name="getUIDPassword">
      <soap:operation soapAction=""/>
      <input>
        <soap:body use="literal" namespace="http://server.kanif.softwaretestingclass.com/"/>
      </input>
      <output>
        <soap:body use="literal" namespace="http://server.kanif.softwaretestingclass.com/"/>
      </output>
    </operation>
  </binding>
  <service name="WebServiceImplementService">
    <port name="WebServiceImplementPort" binding="tns:WebServiceImplementPortBinding">
      <soap:address location="http://localhost:8075/web"/>
    </port>
  </service>
</definitions>
```